

Imexus 34 DS standard equipment and info

DECK

Flexi-Teak cover for deck, deck construction, cockpit floor and bathing platform, 6 mooring cleats, Pulpit, stern basket and guard rail, toe rail, 2 casework winches 2 Genoa winches, self adjusted, wind crank, working winch, self-draining anchor locker, back boxes in the cockpit, Mirror door to bathing platform with ladder, gas cylinders, bilge pump, navigation lights
Shower on swim platform

SAIL

Mainsail about 30 m² with conventional rig rollgross, about 30 m² Genoa match Furler-foresail reefing gear

UV protection for Genoa

RIGGING

Top rigging

Selden rig

double spreader aluminum,

Furler-Roller reefing for foresail

Rodkick with gas pressure spring

BALLAST

Ballast keel

Lead in modern lateral, depth approximately 1.55 m (option for a hydraulic keel available on special order, for price please contact Imexus)

RUDDER

Steering pedestal with integrated compass, steering wheel and gearshift, emergency tiller

Hydraulic steering with steering wheel and gearshift,

ELECTRICAL SYSTEM

Switch board with automatic fuses, warning lights and voltmeter, motor circuit with battery,

Circuit board with battery, shore power connection 230 V, 230 V sockets, inside cabin light

INTERIOR

2 or 3 separate cabins with 4 or 6 berths plus saloon / deck saloon, plenty of storage room, lounge with comfortable outdoor furniture and exhibition tables, sideboards with shelves and cupboards, a wardrobe in front and side cabin

Helm with seating, galley with integrated microwave, gas stove and oven, half-cardanic,

Sink, Storage with drawers and flaps, cooling box with 12 V cooling unit, refrigerator as an option, Bathroom with easy-care surfaces, sink with taps, shower with disposal via electric pump,

Pump toilet with holding tank, Disposal of seacock Twin exhaust, shower in toilet room as an option, Panoramic windows in the living room, plenty of deck hatches to open

Interior heating supply

UPHOLSTERY COLORS AVAILABLE

After samples folder in fabric or Alcantara Optics

FRESH WATER SUPPLY

Fresh water tank with level indicator, electric water pump pressure

Warm water for pantry and kitchen

INSTRUMENTATION

Log, Lit, wind indicator, repeater, Raymarine ST60

Chart plotter with GPS

ENGINE PLANT

Volvo Penta D1-30, 20.1 kW / 27.3 hp (38 hp + 53 hp as an option) with sail drive and fixed propeller, double cooling system with sea water filter, control panel, hour meter, tachometer, alarm buzzer for low oil pressure, cooling water, Charging voltage, insulated engine compartment, fuel tank with level indicator.

Bow thruster 3kw

CE-Certificate "A" Seaworthiness for ocean / open sea